

Product information



SUNOCO

Suniso SL range

Description SUNISO SL grades are synthetic ester lubricants, formulated using select polyolester base stocks and additives providing outstanding lubricity, stability and corrosion protection. These lubricants are miscible in alternative refrigerants such as R-134a at extremely low temperatures.

Application SUNISO SL lubricants have been designed specifically for use in refrigeration and air conditioning systems charged with ozone friendly alternative refrigerants.

Properties

- Miscible in alternative refrigerants such as R-134a, and most other chlorine free HFC refrigerants (such as R-404, R-407c, R-410a, R-507 and R509a/b, etc.), even at extremely low temperatures.
- Provide outstanding lubricity, stability and corrosion protection.

Typical analysis :

	22	32	46	68	100	170	220
Density at 15°C	0.99	0.98	0.97	0.96	0.96	0.97	1.01
Viscosity at 40°C / cSt	22.0	32.0	47.2	70.1	100.0	170	220
Viscosity at 100°C / cSt	4.6	5.8	7.2	9.1	11.3	17.2	20.8
Viscosity index	127	125	120	109	106	108	100
Flash point °C	232	235	235	252	254	260	264
Pour point °C	-48	-48	-44	-36	-36	-24	-30
Water ppm	<100	<100	<100	<100	<100	<100	<100
Colour	L0.5	L0.5	L0.5	L0.5	L0.5	L0.5	L0.5

All technical data is provided for reference only.

8 - 2009